

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/012,195	12/05/2001	Lawrence G. Clawson	3402.1007-000	5684	
21005	7590 02/16/2006		EXAM	INER	
HAMILTON, BROOK, SMITH & REYNOLDS, P.C.			HANDAL,	HANDAL, KAITY V	
530 VIRGINIA P.O. BOX 913			ART UNIT	PAPER NUMBER	
	MA 01742-9133		1764		

DATE MAILED: 02/16/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)	V-
	10/012,195	CLAWSON ET AL.	
Office Action Summary	Examiner	Art Unit	
•			
The MAILING DATE of this communication ap	Kaity Handal	1764	
Period for Reply			
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATIO 136(a). In no event, however, may a reply be ti will apply and will expire SIX (6) MONTHS fror e, cause the application to become ABANDON	N. mely filed n the mailing date of this communication. ED (35 U.S.C. § 133).	
Status			
1)⊠ Responsive to communication(s) filed on 11 J	ulv 2005.		
,	s action is non-final.		
3) Since this application is in condition for allowa	ince except for formal matters, pr	osecution as to the merits is	
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D. 11, 4	53 O.G. 213.	
Disposition of Claims			
4)⊠ Claim(s) <u>1-50</u> is/are pending in the application	l.		
4a) Of the above claim(s) 4,6,9,11-15,20-24, 2	<u>6-29,30-36,38,41,42-48</u> is/are wi	thdrawn from consideration.	
5) Claim(s) is/are allowed.			
6) Claim(s) <u>1-3,5,7,8,10,16-19,25-29,37,39,40,49</u>	9 and 50 is/are rejected.		
7) Claim(s) is/are objected to.	an ala alian na mainana ant		
8) Claim(s) are subject to restriction and/o	or election requirement.		
Application Papers			
9)⊠ The specification is objected to by the Examine	er.		
10)☐ The drawing(s) filed on is/are: a)☐ acc	cepted or b) objected to by the	Examiner.	
Applicant may not request that any objection to the			
Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the E).
Priority under 35 U.S.C. § 119			
12) ☐ Acknowledgment is made of a claim for foreigna) ☐ All b) ☐ Some * c) ☐ None of:	n priority under 35 U.S.C. § 119(a	a)-(d) or (f).	
1. Certified copies of the priority document			
2. Certified copies of the priority document	• •	 	
3. Copies of the certified copies of the price	·	red in this National Stage	
application from the International Burea * See the attached detailed Office action for a list		ad	
See the attached detailed Office action for a list	or the definied doples not receiv	eu.	
Attachment(s)			
1) Motice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summar Paper No(s)/Mail D		
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 10/20/03,10/14/03.	F-1	Patent Application (PTO-152)	

Application/Control Number: 10/012,195 Page 2

Art Unit: 1764

DETAILED ACTION

Election/Restrictions

- 1. Applicant's election of Group II, Species a-2 (claims 1-3, 5, 7-8, 10, 16-19, 25, 27-29, 37, 39, 40, 42-50) in the reply filed on 7/11/2005 is acknowledged. Because applicant did not distinctly and specifically point out the supposed errors in the restriction requirement, the election has been treated as an election without traverse (MPEP § 818.03(a)).
- 2. The examiner further withdraws claims 42-48 from further consideration as they do not read on the elected species. "End caps" are not described under Figure 4 in the Specification.
- 3. The examiner further withdraws claims 27-29 from further consideration as they depend a non-elected claim (claim 26).

Specification

4. The disclosure is objected to because of the following informalities: reference number (215) is used for "coiled tubes" on page 14, line 22; and used for "one expansion bellows" on page 15, line 17.

Appropriate correction is required.

Claim Rejections - 35 USC § 112

5. The following is a quotation of the second paragraph of 35 U.S.C. 112:

Application/Control Number: 10/012,195

Art Unit: 1764

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

6. Claim 8 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Regarding claim 8, it is unclear if oxygen containing gas is preheated in a zone which is different from second zone as claimed in claim 1. For examining purposes, the limitation "a zone", of claim 8, is treated as the "second zone" recited in claim 1.

Claim Rejections - 35 USC § 102

7. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 8. Claims 1-3, 5, 7-8, 10, 16-19, 25, 37, 39-40, 49 and 50 are rejected under 35 U.S.C. 102(b) as being anticipated by Dantowitz (US 3,541,729).

With respect to claims 1 and 7, Dantowitz teaches a reactor/reformer (fig. 1, 1) comprising: a core reaction zone/cylindrical inner wall (45) being configured to conduct exothermic reactions including combustion/partial oxidation/(in burner) (3)), and reforming/(in catalyst bed (31)); shells/walls (13, 47, 71, 85) each having a shell wall (illustrated), the shells/walls (13, 47, 71, 85) being arranged coaxially about the core reaction zone/cylindrical inner wall (45) (illustrated); a gap (illustrated) being defined between each of the shells' walls to form a plurality of coaxial zones

Art Unit: 1764

(illustrated), the reactor/reformer (1) being configured to permit heat transfer directly from one zone to another (illustrated); and the reactor/reformer (1) being configured so that hydrocarbon feed stock/reformable fuel (129) is preheated by traversing a first zone/zone extending between reactant inlet passage (111) and catalyst bed (31) (as illustrated), and an oxygen containing gas/air is preheated/burnt by traversing a second zone/burner (3) (col. 2, lines 47-51).

With respect to claim 2, Dantowitz teaches wherein said reactor/reformer (1) is further configured so that water/steam is preheated in a third zone/boiler reservoir (123).

With respect to claim 3, Dantowitz teaches wherein said reactor/reformer (1) is configured so that water/steam (125) is preheated along with the feedstock/reformable fuel (129) in the first zone/zone extending between reactant inlet passage (111) and catalyst bed (31) (as illustrated).

With respect to claim 5, Dantowitz teaches wherein a burner (3) supplies heat to a steam reforming reaction/catalyst bed (31) in the core reaction zone/burner (3).

With respect to claim 8, Dantowitz teaches wherein said reactor/reformer (1) is configured so that so that oxygen containing gas/air supporting burner combustion is preheated in a zone/second zone/burner (3) (col. 2, lines 47-51).

With respect to claim 10, Dantowitz teaches wherein said reactor/reformer (1) is configured so that exhaust/hot fluid (127) from the burner (3) is flowed through a zone/catalyst heating segment (117) for heat exchange with one or more other zones/catalyst bed (31).

Art Unit: 1764

With respect to claim 16, Dantowitz teaches wherein said reactor/reformer (1) is configured so that said zones have gaps (illustrated).

With respect to claim 19, Dantowitz teaches wherein a steam reformer/reforming catalyst bed (31) (col. 4, lines 48-51) is in the core reaction zone/cylindrical inner wall (45) (illustrated).

With respect to claim 25, Dantowitz teaches a reactor/reformer (1) comprising: shells having walls (13, 47, 71, 85) arranged coaxially (as illustrated) about each other; a gap being defined between each of the successive shells forming a plurality of coaxial zones (illustrated), the shells being configured to permit heat transfer directly from one zone to another; wherein a first zone/cylindrical inner wall (45) is configured to conduct steam reforming (in catalyst bed (31)) (col. 4, lines 48-51) and at least one of the exothermic reactions combustion/partial oxidation/in burner (3); and the reactor/reformer (1) being configured so that hydrocarbon feed stock/ reformable fuel (129) is preheated in a second zone/zone extending between reactant inlet passage (111) and catalyst bed (31) (as illustrated), and an oxygen containing gas/air is preheated/burnt in a third zone/burner (3) (col. 2, lines 47-51).

With respect to claim 37, Dantowitz teaches a reactor/reformer (1) comprising: a plurality of nested shells/walls (13, 47, 71, 85) each having an annular wall and having a gap between each adjacent wall defining a zone (illustrated); said reactor/reformer (1) being configured such that each zone contains a different heat transfer medium/reformate (131) flows within reformate confining wall (85) & water (121) flows through boiler reservoir (123) outer wall (71) & hot fluid (127) flows

Application/Control Number: 10/012,195

Art Unit: 1764

outside cylindrical inner wall (45); and wherein the heat transfer mediums (131, 121, 127) travel through the zones and exchange heat through shell walls (illustrated).

With respect to claim 39, Dantowitz teaches a reactor/reformer (1) comprising a plurality of at least five nested shells/walls (13, 9, 47, 71, 85).

With respect to claim 40, Dantowitz teaches a reactor/reformer (1) comprising:

- a plurality of nested shells/walls (13, 9, 47, 71, 85) having a gap defined between each of the successive shells to form a plurality of coaxial zones between adjacent shells (illustrated);
- a stream of heated material/hot fluid (127) produced by an exothermic reaction including combustion/partial oxidation/burning in burner (3);
- a second stream of heated material/reformate (131) produced by an exothermic reaction/shift reaction (col. 6, lines 73-75 and col. 7, line 1);
- and wherein the streams of heated materials (127 & 131) are each routed as follows: heated material/hot fluid (127) is routed through zone adjacent to zone/frusto-conical baffle wall (17) containing hydrocarbon feedstock/reformable fuel (129); and heated material/ reformate (131) is routed through zone adjacent to zone/boiler reservoir (123) containing steam/water (121).

With respect to claim 49, Dantowitz teaches a reactor/reformer (1) comprising: a plurality of nested shells/walls (13, 9, 47, 71, 85) having walls arranged coaxially and defining a gap between each of the successive shells forming a plurality of coaxial zones (as illustrated), the shells being configured to permit heat transfer from one

Art Unit: 1764

zone to another (as illustrated); and wherein a first zone/cylindrical inner wall (45) contains a catalyst/reforming catalyst bed (31) (col. 4, lines 48-51) and a shift catalyst (col. 6, lines 73-75 and col. 7, line 1); and the reactor being configured so that a hydrocarbon feed stock/reformable fuel (129) is preheated in a second zone/zone extending between reactant inlet passage (111) and catalyst bed (31) (as illustrated), and an oxygen containing gas/air is preheated/burnt by traversing a second zone/burner (3) (col. 2, lines 47-51); and an oxygen containing gas/air is preheated in a third zone/burner (3).

With respect to claim 50, Dantowitz teaches a reactor/reformer (1) comprising: a core reaction zone/shell (9) having an outer wall/cylindrical inner wall (45), the core reaction zone/shell (9) configured to conduct at least one exothermic reaction/shift reaction (col. 6, lines 73-75 and col. 7, line 1) and at least one fuel reforming reaction/in catalyst bed (31) (col. 4, lines 48-51);

at least three shells/walls (47, 71, 85) arranged concentrically about the outer wall of the core reaction zone, a gap being defined between the outer wall of the core reaction zone and each of the successive shells to form a plurality of coaxial zones (illustrated), the shells being configured to permit heat transfer directly between each adjacent zone (illustrated), including the core reaction zone/shell (9);

at least three fluid flows, each in a different coaxial zone/reformate (131) flows within reformate confining wall (85) & water (121) flows through boiler reservoir (123) outer wall (71) & hot fluid (127) flows outside inner reservoir wall (47);

Application/Control Number: 10/012,195 Page 8

Art Unit: 1764

wherein at least two of the fluid flows comprise a reactant (water (121) & reformate (131)) that is pre-heated from an initial temperature to a second temperature suitable for a reaction by traversing a coaxial zone (illustrated), and wherein at least one of the fluid flows/hot fluid (127) comprises a hot product of a reaction that is cooled from an initial elevated temperature to a second cooler temperature by traversing a coaxial zone (illustrated).

9. Claims 1, and 17-18 are rejected under 35 U.S.C. 102(b) as being anticipated by Clawson (WO 98/08771).

With respect to claims 1, Clawson teaches a reactor/reformer (fig. 1, 10) comprising: a core reaction zone (fig. 1, 28&24), the core reaction zone (28 & 24) being configured to conduct exothermic reaction including partial oxidation; shells/vessels (12, 58, 18) each having a shell wall (illustrated), the shells/vessels (12, 58, 18) being arranged coaxially about the core reaction zone (28 & 24) (illustrated); a gap (illustrated) being defined between each of the shells' walls to form a plurality of coaxial zones (illustrated), the reactor/reformer (1) being configured to permit heat transfer directly from one zone to another (illustrated); and the reactor/reformer (10) being configured so that hydrocarbon feed stock/fuel inlet(46) is preheated by traversing a first zone/bottom of helical tube (32), and an oxygen containing gas is preheated by traversing a second zone/top of helical tube (32).

Application/Control Number: 10/012,195 Page 9

Art Unit: 1764

With respect to claims 17-18, Clawson teaches spacers/screens/perforated plates (68) and (30) placed in the zones/reformer vessel (12) and first vessel (30) .

(illustrated) to maintain spacing between successive shells.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kaity Handal whose telephone number is (571) 272-8520. The examiner can normally be reached on M-F 8-5.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Glenn Caldarola can be reached on (571) 272-1444. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

1/31/2006

Walter D. Griffin
Primary Examiner